



DOCKET NO. BABU 1-10-42

PATENT

#3

660803
S-T

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of:

Shivnath Babu, et al.

Serial No.: 10/033,199

Filed: December 28, 2001

For: SYSTEM AND METHOD FOR COMPRESSING
A DATA TABLE USING MODELS

RECEIVED

MAY 27 2003

Group: 2641

Technology Center 2600

Examiner: N/A

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner for Patents, Alexandria, VA 22313, on

May 20, 2003 (Date)

Shivnath Babu (Printed or typed name of person signing the certificate)

Shivnath Babu (Signature of the person signing the certificate)

Sir:

LETTER TO OFFICIAL DRAFTSMAN

Transmitted herewith are eight sheets of formal drawings to be substituted for the informal drawings initially filed in the above-identified application for patent.

Respectfully submitted,

HITT GAINES & BOISBRUN, P.C.

David H. Hitt
Registration No. 33,182

Date: MAY 19, 2003


P.O. Box 832570
Richardson, Texas 75083
(972) 480-8800



System and Method for Compressing a Data Table
Babu 1-10-42
Serial No.: 10/033,199
Hitt, Gaines & Boisbrun, PC; (972) 480-8800

1 / 8

FIG. 1





System and Method for Compressing a Data Table
Babu 1-10-42
Serial No.: 10/033,199
Hitt, Gaines & Boisbrun, PC; (972) 480-8800

2/8

FIG. 2

The Greedy CaRT Selection Algorithm

```
procedure Greedy (T(X) ,  $\bar{e}$ , G,  $\theta$ )
Input: n-attribute table T and n-vector of error tolerances  $\bar{e}$ ;
       Bayesian network G on the set of attributes X and
       threshold  $\theta$  on the relative benefit for selecting a
       CaRT predictor.
Output: A set of materialized (predicted) attributes  $X_{mat}$  ( $X_{pred} = X - X_{mat}$ ) and a CaRT predictor for each  $X_i \in X_{pred}$ .
begin
  1.  $X_{mat} := X_{pred} := \emptyset$ 
  2. let  $\langle X_1, X_2, \dots, X_n \rangle$  be the attributes in X sorted in
     topological order of G
  3. for i := 1, ..., n
  4. if  $\Pi(X_i) = \emptyset$  then  $X_{mat} := X_{mat} \cup \{X_i\}$  /*  $X_i$  must be
     materialized if it has no parents in G */
  5. else
  6.   M := BuildCaRT ( $X_{mat} \rightarrow X_i$ ,  $e_i$ )
  7.   if ( $MaterCost(X_i) / PredCost(X_{mat} \rightarrow X_i) > \theta$ ) then  $X_{pred} :=$ 
      $X_{pred} \cup \{X_i\}$ 
  8. else  $X_{mat} := X_{mat} \cup \{X_i\}$ 
  9. end
 10. end
end
```



System and Method for Compressing a Data Table
Babu 1-10-42
Serial No.: 10/033,199
Hitt, Gaines & Boisbrun, PC; (972) 480-8800

3/8

FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D






FIG. 4

The MaxIndependentSet CaRT Selection Algorithm

```

procedure MaxIndependentSet (T(X) ,  $\bar{e}$ , G, neighborhood() )
Input: n-attribute table T and n-vector of error tolerances  $\bar{e}$ ;
       Bayesian network G on the set of attributes X and function
       neighborhood () defining the "predictive neighborhood" of a
       node  $X_i$  in G (e.g.,  $\Pi(X_1)$  or  $\beta(X_i)$ ).
Output: A set of materialized (predicted) attributes  $X_{mat}$  ( $X_{pred} = X -$ 
        $X_{mat}$ ) and a CaRT predictor  $PRED(X_i) \rightarrow X_i$  for each  $X_i \in X_{pred}$ .
begin
    1.  $X_{mat} := X$ ,  $X_{pred} := \emptyset$ 
    2.  $PRED(X_i) := \emptyset$  for all  $X_i \in X$ , improve := true
    3. while (improve  $\neq$  false) do
    4.     for each  $X_i \in X_{mat}$ 
    5.         mater_neighbors ( $X_i$ ) :=  

            $(X_{mat} \cap \text{neighborhood}(X_i)) \cup \{PRED(X) : X \in \text{neighborhood}(X_i), X \in X_{pred}\} - \{X_i\}$ 
    6.         M := BuildCaRT (Mater_neighbors ( $X_i$ )  $\rightarrow X_i$ ,  $e_i$ )
    7.         let  $PRED(X_i) \subseteq \text{mater_neighbors}(X_i)$  be the set of
           predictor attributes used in M
    8.         cost_change $_i$  := 0
    9.         for each  $X_j \in X_{pred}$  such that  $X_j \in PRED(X_i)$ 
    10.            NEW_PRED $_i(X_j)$  :=  $PRED(X_j) - \{X_i\} \cup PRED(X_i)$ 
    11.            M := BuildCaRT (NEW_PRED $_i(X_j)$   $\rightarrow X_j$ ,  $e_j$ )
    12.            set NEW_PRED $_i(X_j)$  to the (sub) set of
           predictor attributes used in M
    13.            cost_change $_i$  := cost_change $_i$  + (PredCost (PRED
           ( $X_j \rightarrow X_j$ ) - PredCost (NEW_PRED $_i(X_j) \rightarrow X_j$ ))
    14.        end
    15.    end

```



FIG. 4 (cont)

```
16. build an undirected, node-weighted graph  $G_{temp} = (X_{mat},$   
17.  $E_{temp})$  on the current set of materialized  
18. attributes  $X_{mat}$ , where:  
19. (a)  $E_{temp} := \{ (X, Y) : \text{for all pairs } X, Y \in X_{pred} \} \cup$   
20.  $\{ (X_i, Y) : \text{for all } Y \in X_{mat} \}$   
21. (b)  $\text{weight}(X_i) := \text{MaterCost}(X_i) - \text{PredCost}(\text{PRED}(X_i))$   
22.  $\rightarrow X_i) + \text{cost\_change}_i$  for each  $X_i \in X_{mat}$   
23.  $S := \text{FindWMIS}(G_{temp})$  /* select (approximate) maximum  
24. weight independent set in  $G_{temp}$   
25. as "maximum-benefit" subset of  
26. predicted attributes */  
27. if  $(\sum_{X \in S} \text{weight}(X) \leq 0)$  then improve := false  
28. else /* update  $X_{mat}$ ,  $X_{pred}$ , and the chosen CaRT predictors */  
29. for each  $X_j \in X_{pred}$   
30. if  $(\text{PRED}(X_j) \cap S = \{X_i\})$  then  $\text{PRED}(X_j) :=$   
end  $\text{NEW\_PRED}_i(X_j)$   
end  
31.  $X_{mat} := X_{mat} - S$ ,  $X_{pred} := X_{pred} \cup S$   
end  
32. end /* while */  
end
```

FIG. 5

Algorithm for Estimating Lower Bound on Subtree Cost

```
procedure LowerBound (N, ej, b)
Input: Leaf N for which lower bound on subtree cost is to be
       computed; error tolerance ej for attribute Xj; bound b
       on the maximum number of internal nodes in subtree
       rooted at N.
Output: Lower bound L(N) on cost of subtree rooted at N.
begin
  1. for i := 1 to r
  2.   minOut [i, 0] := i
  3. for j := 1 to b + 1
  4.   minOut [0, j] := 0
  5. 1 := 0
  6. for i := 1 to r
  7.   while xj - xj+1 > 2 ej
  8.   1 := 1 = 1
  9.   for j := 1 to b + 1
 10.    minOut [i,j] := min {minOut[i - 1,j] + 1, minOut [1,j-1]}
 11. end
 12. L(N) := ∞
 13. for j := 0 to b
 14.   L(N) := min {L(N) , 2j + 1 + j log (|Xj|) + (j + 1 + minOut
       (r, j+1)) log (|dom(Xj)|)}
 15. L(N) := min {L(N) , 2b + 3 + (b + 1) log (|Xj|) + (b + 2) log
       (|dom(Xj)|) }
 16. return L (N)
end
```








System and Method for Compressing a Data Table
Babu 1-10-42
Serial No.: 10/033,199
Hitt, Gaines & Boisbrun, PC; (972) 480-8800

7/8

FIG. 6





System and Method for Compressing a Data Table
Babu 1-10-42
Serial No.: 10/033,199
Hitt, Gaines & Boisbrun, PC; (972) 480-8800

8/8

FIG. 7A




FIG. 7B




FIG. 7C

